

# Bombas Circuladoras



	$I_{max}$	$P_{max}$
1	0,14	33
2	0,17	39
3	0,19	44



**HUPA 25-4.0 U 180**

230 V ~ 50 Hz  
PN 10, IP 44, TF 110, Class F

Halm Pumpen + Motoren GmbH & Co. KG / Germany



# Especificaciones Técnicas



HUPA



HHPA



HGPA



BUPA



BGPA

Códigos	Circuladoras Calefacción / Solar			Conexión	Potencia Watt	Modelos Compatibles		
						Wilo	Dab	
500001	HUPA	25-4.0 / 180	Fe	1"	44	STAR-RS 25/4	VA	35/180
500002	HUPA	25-6.0 / 180	Fe	1"	80	STAR-RS 25/6	VA	55/180
500003	HUPA	30-7.0 / 180	Fe	1 1/4"	93	STAR-RS 30/6	VA	65/180
500004	HUPA	25-4.0 / 130	Fe	1"	44	STAR-RS 25/4	VA	35/130
500350	HUPA	15-7.0 / 130	Fe	1/2"	93	—	—	—
500005	HUPA	25-7.0 / 130	Fe	1"	93	STAR-RS 25/6	VA	65/130
500050	HHPA	30-7.0 / 180	Fe	1 1/4"	190	TOP-S 30/7	A	50/180
500051	HGPA	30-8.0 / 180	Fe	1 1/4"	286	TOP-S 30/10	A	80/180
500052	HGPA	30-12.0 / 180	Fe	1 1/4"	400	—	A	110/180

  

Códigos	Circuladora Sanitaria			Conexión	Potencia Watt	Modelos Compatibles		
						Wilo	Dab	
500301	BUPA	20-4.0 / 150	Inox	3/4"	70	STAR-Z 20/1	VS	35/150
500302	BUPA	20-6.0 / 150	Inox	3/4"	100	ATAR-Z 20/2	VS	65/150
500303	BUPA	25-6.0 / 130	Bronce	1"	70	ATAR-Z 20/2	VS	65/150
500053	BGPA	25-8.0 / 180	Inox	1"	286	—	ALP	800 M

